




US 20150164172A1

(19) **United States**(12) **Patent Application Publication**
Linares et al.(10) **Pub. No.: US 2015/0164172 A1**(43) **Pub. Date: Jun. 18, 2015**(54) **HELMET FOR ATTENUATING IMPACT
EVENT****Publication Classification**(71) Applicant: **Linares Medical Devices, LLC**, Auburn
Hills, MI (US)(51) **Int. Cl.**
A42B 3/06 (2006.01)(72) Inventors: **Miguel A. Linares**, Bloomfield Hills, MI
(US); **Miguel A. Linares, JR.**,
Bloomfield Hills, MI (US)(52) **U.S. Cl.**
CPC **A42B 3/06** (2013.01)(73) Assignee: **Linares Medical Devices, LLC**, Auburn
Hills, MI (US)(57) **ABSTRACT**(21) Appl. No.: **14/575,170**(22) Filed: **Dec. 18, 2014****Related U.S. Application Data**(60) Provisional application No. 61/917,708, filed on Dec.
18, 2013.

A force attenuating helmet construction including a rigid layer generally conforming to the wearer's head. A plurality of force absorbing and reacting portions extend from locations of the rigid layer such that, in response to an impact event experienced by the helmet, the absorptive and reactive forces minimize impact forces transferred to the user's head and spine. The helmet can include inner and outer rigid layers, or shells, and which are spatially supported by a plurality of force attenuating components.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20

FIG. 21









FIG. 22





HELMET FOR ATTENUATING IMPACT EVENT

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This Application claims the benefit of U.S. Provisional Application 61/917,708 filed on Dec. 18, 2013, the contents of which are incorporated herein in its entirety.

FIELD OF THE INVENTION

[0002] The present invention is directed to a variety of helmet designs incorporating active force cushioning and redirection structure for absorbing the effects of an impact event in a manner which minimizes damage to the wearer's skull and upper cervical spinal vertebrae. In particular, the present inventions include a first helmet incorporating a plurality of inner supported ballasting and force absorption components integrated into the helmet. This includes each of a top/crown mounted pancake style cylinder for protecting the top of the head, an upper inner perimeter encircling ring array of impact baffle portions for protecting the skull, a pair of cheek/zygomatic bone cushioning supports, each of these incorporating a bunch of stem supported and modified bulbous deflecting portions.

[0003] Also incorporated into the first helmet configuration are a plurality of three lowermost periphery mounted spring supported portions extending externally about the sides and rear of the lowermost edge of the helmet. An inner extending and lower rear head support portion is located below the upper perimeter ring array for protecting the rear base of the skull and spinal column.

[0004] A further helmet embodiment incorporates inner and outer rigid layers or shells, between which are supported a variety of cushioning force absorption and redirection components. Mounting locations of an associated face mask to sides of the outer helmet can also include pairs of bidirectional compression springs for providing bi-directional force dissipating displacement of the mask, such as in response to a pulling or pushing force.

BACKGROUND OF THE INVENTION

[0005] The prior art is documented with numerous examples of impact absorbing and protecting helmet designs. The objective in each instance is to provide a head and neck protection to the wearer.

[0006] A first example is the shock balance controller of Harris, U.S. Pat. No. 7,603,725 and which teaches a support structure having a chamber including a port disposed in a side of the chamber, the port providing an opening to a housing, and a bladder coupled to the housing, the bladder being filled with a first material configured to receive pressure from a shock, wherein the first material, when receiving the shock pushes a first piston that compresses a spring disposed in the housing, the spring pushing a second piston that increases the pressure of a second material stored in the chamber. A shock balance controller may also include a structure configured to support the shock balance controller, the structure having a chamber, a port, and a housing assembly, and a bladder coupled to the structure using the housing assembly, the bladder and housing assembly being configured to transfer energy between the bladder and the chamber.

[0007] Anderson, US 2013/0312161, teaches an impact energy attenuation material, impact energy attenuation mod-

ule employing the material and a fit system for optimizing the performance thereof is provided. Non-linear energy attenuating material consisting of a plurality of loose particles is employed for impact energy dissipation. The loose particles are preferably spherical elastomeric balls. An impact energy attenuation module includes a container that holds the loose particles. The impact energy attenuation module can be provided in a wide range of sizes and shapes and the loose particles can be provided in different materials, sizes, density, compaction and hardness to suit with the application at hand. A matrix of impact energy attenuation module are provided about the surface of a shell to provide the required impact energy attenuation. The material, impact energy attenuation module and system of the present invention are well suited for protection of body parts and other cushioning and protection needs.

[0008] Abernathy, U.S. Pat. No. 8,739,317, teaches a liner adapted to be interposed between the interior surface of a protective headgear and a wearer's head and includes a plurality of networked fluid cells adapted to distribute and dissipate an impact force to the liner, and/or headgear with which the liner is used, across a larger area of the wearer's head as compared with the impact location, and also to dampen the tendency of the wearer's head from rebounding back from the impact location by transferring fluid through the network from fluid cells at the impact location to those in an opposed region. Discrete fluid cells interspersed among the networked fluid cells maintain the liner and/or the headgear in a predetermined orientation on the wearer's head. Fluid flow within the liner may be restricted or directed by configuring the fluid passageways. A liner may further include means for moving fluid into or out of the fluid cells.

[0009] Suddaby, US 2014/0173810, teaches a protective helmet having multiple zones of protection suitable for use in construction work, athletic endeavors, and similar activities. The helmet includes a hard outer protective that is suspended over a hard anchor zone by elastic bladders are positioned in the elastomeric zone and bulge through one or more of a plurality of apertures located in the outer zone. In one embodiment, an additional crumple zone is present. The structure enables the helmet to divert linear and rotational forces away from the user's braincase.

[0010] Also referenced is the helmet structure of Brown, US 2014/0068841, without any hard outer shell and which has axially compressible cell units contained in a hemispheric frame by a thin fabric covering stretched over cup shaped cell retainers that have sidewalls of compressible foam. The frame is supported on the wearer's head on plastic foam posts that space the inner ends of compressible bladders from the wearer's head, and ambient air in the bladders compresses at impact, being vented then through openings for gradually absorbing such impact forces. Each bladder is vented into a space between the cup "bottom" and the outer end of a bladder. At least two cell sizes are provided, and some of these are on depending lobes in the frame, for protecting the wearer's ears and neck.

SUMMARY OF THE INVENTION

[0011] The present invention teaches a force attenuating helmet construction including a rigid layer generally conforming to the wearer's head. A plurality of force absorbing and reacting portions extend from locations of the rigid layer such that, in response to an impact event experienced by the

helmet, the absorptive and reactive forces minimize impact forces transferred to the user's head and spine.

[0012] The force absorbing and reacting portions further include at least one exterior mounted cushioning member supported along a lower rim edge of the rigid layer via a plurality of dynamic force absorbing and counter exerting springs. This can further include a plurality of three cushioning portions, each exhibiting an inner contoured surface from which extends the springs in spaced apart fashion, the cushioning members collectively projecting from the lower rim of a rigid wearable shell in a manner which facilitates attenuating the bending motions of the user's head relative to the neck and spine which are associated with an impact event.

[0013] Other features include a combination of internal supported cushioning components associated with the rigid layer and including at least one of a top inner located compressible bladder, an inner and intermediate extending cushioning ring, a pair of cheek (zygomatic) bone located cushioning support members, and a lower and rear perimeter extending ring supported upon the inside of the rigid layer. The top inner bladder may further exhibit a pseudo pancake configuration with upper and lower flattened portions which are interconnected by an intermediate bridging stem portion, the top inner bladder providing controlled collapse and reformable valving structure such that a hollow interior associated with the bladder deforms in a force attenuating fashion, following which it self-refills and resets with a ballasting fluid.

[0014] The intermediate extending cushioning ring further includes a plurality of individual collapsible portions provided in a circular ring array, each of the collapsible portions exhibiting a soft plastic or like material and which includes a baffled or controlled collapsing structure. The innermost portion associated with the lower spring biased cushioning member further has an outer foam or like body which encapsulates a plurality of interconnected interior baffles formed in a generally arcuate array, a series of vents or valve locations being formed in spaced fashion around the body and which respond to compression resulting from the impact event by discharging air or like fluid in a controlled collapsible and force attenuating fashion.

[0015] Yet additional features include the pair of cheek (zygomatic) bone located cushioning support members each further having a planar base, from an inner surface of which projects an array of stem supported compressible portions upon which are mounted increased diameter annular portions. In response to compressive forces exerted by the wearers cheek bones to the pad shaped cushioning members, the end-mounted annular portions deform in a collective combined bending and compressing fashion such that the force of the cheek bone causes the stem supported portions to increase (widen) their collective diameter dimensions in a counter force attenuating fashion.

[0016] Other features include the rigid layer further defining an inner rigid layer with inner support locations which are configured to closely conform to the user's skull, and outer spaced rigid layer being resiliently secured to the inner rigid layer via a plurality of flexible and elastic support tendons extending between the spaced apart inner and outer rigid helmet layers such that, in response to an impact event, the outer rigid layer deflecting relative to the inner layer by virtue of either stretching or compressing one or more selected support tendons. The elastic support tendons each further exhibit a generally polygonal cross sectional shaped interme-

diate stem terminating in flattened engaging portions which can be mechanically or chemically secured to opposing surface locations of the outer and inner rigid layers.

[0017] Yet additional embodiments include the outer spaced rigid helmet layer being resiliently secured to the inner rigid helmet layer via a structural force absorbing foam insert positioned or arranged in spatially defining fashion between the inner and outer rigid layers. Additional spatially supporting and force absorbing components can also be provided in the form of plasticized supporting components such as including a column support extending between the layers and, upon the outer helmet experiencing an impact event, providing for multi-directional energy absorbing properties.

[0018] Other reconfigurations of the inner/outer helmet spatially supporting/force absorbing components include each of an outer disk, an outer disk in combination with an inner integrally configured cross configuration, an internally hollow sphere, and an arrangement of first and second disks configured in rotatably offset and overlapping/intersecting fashion. Further features include a face mask mounted at multiple locations to the outer helmet and incorporating a dual compression spring arrangement associated with each mounting location for bi-directional force absorbing displacement.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] Reference will now be made to the attached drawings, when read in combination with the following detailed description, wherein like reference numerals refer to like parts throughout the several views, and in which:

[0020] FIG. 1 is a perspective view of a helmet construction according to a first embodiment and illustrating a ventilated outer shell in combination with a lower rim projecting and spring biased cushioning member for attenuating the bending motions of the head relative to the neck and spine which are associated with an impact event;

[0021] FIG. 2 is a perspective view of the helmet of FIG. 1 removed and which illustrates a combination of additional and internal cushioning components associated with the present design and including a top inner located compressible bladder in combination with an inner and intermediate extending cushioning ring, along with cheek (malar or zygomatic) bone located cushioning support members;

[0022] FIG. 3 is an underside rotated view of the helmet in FIG. 1 and illustrating the combination of inner cushioning components of FIG. 2 in combination with the outer lower rim cushioning member;

[0023] FIG. 4 is a spatial perspective arrayed illustration similar to FIG. 2 with the wearer's head, neck and upper extremities removed and better illustrating the support configuration collectively provided by the collection of inner and outer supporting portions in combination with the hard shell;

[0024] FIG. 5 is an enlarged view of a selected cheek (zygomatic) bone located cushioning support member and better exhibiting the inner surface projecting array of stem supported compressible portions which respond to compressive forces by bending and/or collapsing in combination with increasing their collective diameter dimensions in a counter force attenuating fashion;

[0025] FIG. 6 is a phantom perspective of an innermost portion associated with the lower spring biased cushioning member and which exhibits interior baffles with control collapse venting, around which is configured a soft foam material;

[0026] FIG. 7 is an enlarged perspective of the inner intermediate extending cushioning ring and which likewise illustrates control collapse baffling structure for responding to compressive forces associated with an impact event;

[0027] FIG. 8 is a side illustration showing the rigid helmet in partial phantom and illustrating the pseudo pancake configuration of the top inner located compressible bladder with upper and lower flattened portions and intermediate bridging stem portion;

[0028] FIG. 9 is an environmental illustration of the helmet of FIG. 1 responding to a side impact event and in which the lower rim extending spring biasing members cushion in counterforce generating fashion against a shoulder of the wearer;

[0029] FIG. 10 is an environmental illustration of a front impact event and in which the rear spaced rim extending spring biased member cushions in counterforce generating fashion against the upper back and based of the cervical portion of the spinal column;

[0030] FIG. 11 is a further environmental illustration of a rear impact event in which forward terminating ends of a pair of outermost spaced and rim extending cushioning members bias in counterforce generating fashion against locations of the wearer's collar bone;

[0031] FIG. 12 is an environmental front view of a dual layer helmet construction according to a second embodiment and illustrating a plurality of flexible and elastic support tendons extending between the spaced apart inner and outer rigid helmet layers;

[0032] FIG. 13 is a side line art view of the dual layer helmet of FIG. 12 and illustrating an arrangement of the inner bridging support tendons between the inner and outer rigid layers;

[0033] FIG. 14 is a side cutaway of the helmet of FIG. 12;

[0034] FIG. 15 is a succeeding view to FIG. 14 and illustrating the dynamic deflecting characteristics of the elastic tendon supported outer helmet in response to a forward impact event;

[0035] FIG. 16 is an alternate view to FIG. 15 illustrating the dynamic deflecting characteristics of the elastic tendon supported outer helmet in response to a rear impact event;

[0036] FIG. 17 is an alternate view to FIGS. 15 and 16 and illustrating a side impact event;

[0037] FIG. 18 is an illustration of a dual layer helmet construction according to a third embodiment and illustrating a foam insert positioned between the inner and outer rigid layers alternative to the support tendons shown in FIG. 12;

[0038] FIG. 19 is a cutaway view of the helmet shown in FIG. 18 and better illustrating the inner and outer rigid helmet layers, intermediate foam support with interior air circulation and venting characteristics, and the inner cushioning pad support configured between the inner rigid helmet layer and the surface of the wearers head;

[0039] FIG. 20 is a succeeding illustration to FIG. 19 and illustrating the dynamic characteristics of the helmet in response to a side-impact event;

[0040] FIG. 21 illustrates a further partial illustration of a dual layer helmet according to a yet further variant and further showing an energy absorbing column support extending between the layers and, upon the outer helmet experiencing an impact event, providing for multi-directional energy absorbing properties;

[0041] FIG. 22 is a further rotated partial perspective in cutaway of the helmet of FIG. 21 and illustrating a dual compression spring arrangement associated with a given face

mask mounting location with the outer helmet, such providing for bi-directional force absorbing displacement;

[0042] FIG. 23 is a front view of a related helmet construction to that depicted in FIG. 21 and illustrating a modified construction of a force absorbing component arranged in combination with the energy absorbing column support for supporting the inner and outer helmet layers in spatial fashion, the additional component exhibiting an outer disk for providing optimal force deflection/absorption of impact forces exerted against the outer helmet;

[0043] FIG. 24 is partial frontal side illustration of a modification of the force absorbing component in the form of an outer disk in combination with an inner integrally configured cross configuration for providing optimal force deflection/absorption of impact forces exerted against the outer helmet;

[0044] FIG. 25 is a similar view to FIG. 24 and depicting a selected force absorbing component in the configuration of an internally hollow sphere; and

[0045] FIG. 26 presents a yet further variant of force absorbing component in the form of first and second disks arranged in rotatably offset and overlapping/intersecting fashion.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0046] As previously described, the present invention is directed to a variety of helmet designs incorporating active force cushioning and redirection structure which is constructed in order to both absorb and actively redirect the effects of an impact event in a manner which minimizes damage to the wearer's skull and upper cervical spinal vertebrae. The helmet designs, described in more detail with reference to FIGS. 1-26, are further constructed to provide enhanced force absorption associated with an impact event, combined with dynamic counter force generating, or reactive, properties (such as which are facilitated by springs or other internal structure) to further ameliorate the effects of the resultant forces resulting from the impact event.

[0047] FIG. 1 is a perspective view, generally at 10, of a helmet construction according to a first embodiment which is worn upon the head of an individual 2. As also illustrated in FIG. 3, the helmet includes a rigid outer shell 12 and which is appropriately configured so as to be placed over the head of the wearer and illustrating appropriate ventilated locations, see inner rim defined apertures 14, 16, 18 et seq., formed in an upper or crown portion of the rigid shell. Additional apertures in the rigid shell are provided, such as ear hole locations at 19. Without limitation, the shell 12 can be constructed of any type rigid and impact resistant plastic, carbon fiber or composite thereof.

[0048] As best shown by the underside rotated perspective of FIG. 3, a lower rim projecting cushioning member is provided and includes one or more (three shown) rim extending portions 20, 22 and 24 which are secured to lower rim extending locations of the rigid shell 12 via individual sets of support springs, these shown in FIG. 1 by springs 26 and 28 for supporting cushioning portion 20, springs 30, 32 and 34 (FIG. 4) for supporting cushioning portion 22, and finally springs 36 and 38 for cushioning portion 24. The springs are supported upon inner contoured surfaces of each cushioning member 20, 22 and 24 in spaced apart fashion (as again best shown in FIG. 4) and so that the spring biased cushioning members collectively project from the lower rim of the rigid wearable shell 12 in a manner which facilitates attenuating

the bending motions of the head relative to the neck and spine which are associated with an impact event, and as will be further described.

[0049] Without limitation, the cushioning portions **20**, **22** and **24** can be constructed of any semi-soft or other suitable material, such as which can include an inner support portion, around which can be formed an outer cushioning portion. As further best shown in FIG. 4, the cushioning portions **20**, **22** and **24** each exhibit an arcuate elongated configuration with a substantially “U” shape in cross section. As shown, the intermediate/middle cushioning portion **22** exhibits an open channel along its entire arcuate lengths, the with outer portions **20** and **24** having closed front ends, see at **21** and **25**, respectively, and which overlay the bottom rim of the rigid shell **12** at the front side locations.

[0050] As further shown, the springs **26-38** anchor to exterior lower rim proximate locations of the rigid shell **12** and extend outwardly (and as further shown in FIG. 4 in a slightly upwardly angled fashion) to inner side locations of each “U” shape configuration in order to support the cushioning portions **20**, **22** and **24**. This can further include the outwardly projecting ends of the springs being anchored to the inner support portion of each cushioning member and, in this manner, the cushioning portions are adequately structurally supported to the helmet’s rigid shell in a force absorbing and counter force generating fashion. Alternative to the springs shown, it is also envisioned that any other cushioning member supporting and counterforce generating components can be utilized, these not limited to any other type of spring, air pressure generating/cushioning device or the like.

[0051] FIG. 2 is a perspective view similar to FIG. 1 with the rigid shell **12** removed and which illustrates a combination internal cushioning components associated with the present design. These include such as a top inner located compressible bladder, generally at **40** (also termed a pancake bladder as will be further described), in combination with an inner and intermediate extending cushioning ring **42** about an upper perimeter/periphery of the skull, and along with cheek (zygomatic) bone located cushioning support members (pair at **44**). Additional internal cushioning components include a lower and rear perimeter extending ring **46** supported upon the inside of the rigid shell **12** for supporting the rear base of the skull and the upper connecting location of the spinal column.

[0052] As shown in each of FIGS. 2-4 and, as best shown in the phantom side illustration of FIG. 8, the bladder **40** exhibits a pseudo pancake configuration with upper **48** and lower **50** flattened portions which are interconnected by an intermediate bridging stem portion **52**. The top inner pancake style bladder is intended to provide cushioning for the top of the wearer’s head and, as described above, can incorporate any style of inner cylinder or air intake/outflow bladder as well as any other style of controlled collapse and reformable valving structure such that the body with hollow interior can deform in a force attenuating fashion, following which it self-refills and resets with a ballasting air volume. Although not shown, the pancake bladder can include any other configuration of bi-directional valving for communicating the exterior of the bladder to its hollow interior and in order to provide controlled collapsing discharge in response to a top head impact event, in combination with subsequent self-refilling and re-expansion of the bladder.

[0053] The material construction of the top pancake bladder **40** is further such that it can be formed of any soft plastic

(can also include but is not limited to a thermoplastic elastomer or thermoplastic vulcanizate) or can include other suitable material including any type of solid (including a foam) or other suitable material. Other features associated with the pancake style bladder include the ability to substitute the air vent and valve structure with any other fluid medium. This can further include utilizing a liquid coolant as a force attenuating medium for any or all of the inner helmet cushioning portions and which can provide the dual function of assisting in cooling the head of the wearer. Alternately, and in very cold weather (environment) sport or non-sport applications, the liquid held within the bladder or other cushioning member can provide for warming/heating of the wearer’s head.

[0054] The inner and intermediate extending cushioning ring **42** is best shown in FIG. 7 and which likewise illustrates control collapse baffling structure for responding to compressive forces associated with an impact event. A plurality of individual collapsible portions, at **54**, **56**, **58** et seq., are provided in a circular ring array. Each of the collapsible portions exhibits a soft plastic or like material and which includes a baffled or controlled collapsing structure as depicted by valves or vents **60**, **62** and **64**, respectively, these further being shown in alternating top and bottom depiction associated with selected individual portions **54**, **56**, **58**, et seq.

[0055] The cross sectional profile of the intermediate cushioning ring array is best depicted in FIG. 7 in line art depiction, with the understanding that this can also depict an inner circular support structure provided by spaced apart and circular extending wires or tensioning cables **64** and **66**, between which are configured crosswise extending and spaced apart (interconnecting) wires or cables **68**, **70**, **72** et seq. As shown, the configuration of a suitable support structure is such that it provides additional connecting and reinforcing support to the skull encircling cushion ring **42**, the perimeter surrounding cable configuration corresponding to the profile of the individual collapsible portions **54**, **56**, **58** et seq., such that the structure can provide an additional degree of structural support to the assembly. Without limitation, the cable extending support structure shown can alternately include the use of plastic tensioning elements which can be in-molded with the intermediate cushioning ring array **42** in order to provide structural integrity to the array.

[0056] As with the top pseudo pancake style bladder **40**, the intermediate cushioning ring can incorporate controlled collapse and refill/reform properties utilizing any type of fluid medium (air, liquid etc.) and which establishes a desired degree of force attenuation/counter force generating functionality. The intermediate/cushioning ring array **42** can also be constructed of any type of compressible gel or foam. The cushioning ring **42** (also termed an impact pad) can also be produced individually or in combination with either or both of the face pads **44** or the lower inner rim extending cushioning ring **46**.

[0057] As best shown in FIG. 6, a phantom perspective of an innermost portion associated with the lower spring biased cushioning member **46** is shown and includes an outer foam or like body **74** which encapsulates a plurality of interconnected interior baffles, these illustrated in phantom and being formed in a generally arcuate extending array **76**. As with the intermediate band, control collapse of the baffle structural array **76** is provided by a series of vents or valve locations **78**, **80**, **82** et seq. formed in the manner shown and which respond to compression resulting from the impact event by discharging air or like fluid in a controlled collapsible and force

attenuating fashion (following which the baffle or bladder structure 76 can refill/reform to its original configuration in a manner consistent with the valving structure depicted in combination with the other cushioning/force absorbing components).

[0058] Similar to the intermediate circular cushioning ring 42, the cross sectional profile of the lower and inner rim extending cushioning member 46 is depicted in line art in FIG. 6 (see irregular lines 84 and 86 depicting the inner and outer undulating walls of the baffle construction with additional outer 88 and inner lines 90 representing the foam edges). The lower extending cushioning member 46 can also include, without limitation, any type of structural support (such as including an inner wire, tensioning element or spine) to assist in providing structural integrity and so that, in combination, the lower rear head supporting member 46 cushions the back of the head and the upper end of the spinal column through the provision of a sandwich construction of elements which can include a mixture of air and foam or other soft material.

[0059] As further best shown in FIG. 5, an enlarged view is depicted of a selected one of the pair of cheek (zygomatic) bone located cushioning support members, again shown at 44 and which better exhibits an inner surface projecting array of stem supported compressible portions, see stems 92, 94, 96, et seq., and upon which are mounted upper extending end and increased diameter annular portions 98, 100, 102, et seq. (in informal terms these each illustrating an overall configuration not dissimilar to a bishop associated with a chess set). The construction of the stem supported and compressible portions is such that, in response to compressive forces exerted by the wearers cheek bones to the pad shaped cushioning members 44, the end-mounted annular portions 98, 100, 102, et seq. (these including semi-spherical shaped ends 104, 106, 108, et seq.) deform in a collective combined bending and compressing/widening fashion such that the force of the cheek/zygomatic bone causes the stem supported portions to increase (widen) their collective diameter dimensions in a counter force attenuating fashion.

[0060] As a result, the compressed and flattened portions (see again stems 92, 94, 96, et seq.) progressively exert counter actuating forces against the wearer's face during their collapse with the additional feature being the flattening of the enlarged ends 104, 106, 108, et seq. in a manner which creates a maximum collapse/compression distance which is a dimension above the inner support surface of the member 44. Without limitation, the cheek located support members 44 can be substituted or augmented by additional members located at any other interior supported location of the rigid shell of the helmet.

[0061] As previously described, FIG. 3 is an underside rotated view of the helmet in FIG. 1 and illustrates the combination of inner cushioning components of FIG. 2 in combination with the outer lower rim cushioning member, with FIG. 4 further providing a spatially perspective arrayed illustration similar to FIG. 2 with the wearer's head, neck and upper extremities removed and better illustrating the support configuration collectively provided by the collection of inner and outer supporting portions in combination with the hard shell.

[0062] Proceeding to the environmental view of FIG. 9, an environmental illustration is shown of the helmet of FIG. 1 responding to a side impact event (see directional arrow 110) and in which a selected one of the lower rim extending spring

biasing cushions (shown at 20) is exerted in a counterforce generating fashion against a shoulder 4 of the wearer, again by virtue of the absorbing and reasserting forces exerted by springs 26 and 28. FIG. 10 is an environmental illustration of a front impact event, see directional arrow 112, and in which a rearmost selected 22 of the rim extending spring biased member cushions with associated springs 30 and 32 contact the wearers back 6 in proximity to the cervical portion of the spinal column. Finally, FIG. 11 is an illustration of a rear located impact (see arrow 114) in which forward ends 116 and 118 outer rim located cushioning members 20 and 24 contact collarbone locations 8 and 9 of the wearer in a flexible and force attenuating fashion.

[0063] Referring now to FIG. 12, an environmental front view is generally shown at 120 of a dual layer helmet construction according to a second embodiment of the present inventions. The helmet includes an inner rigid layer or shell 122 configured to closely conform to the user's skull, with an outer spaced rigid layer or shell 124 which is resiliently secured to the inner rigid layer 122 via a plurality of flexible and elastic support tendons or spatially defining columns (see pair at 126 and 128) extending between the spaced apart inner 122 and outer 124 rigid helmet layers.

[0064] Either or both the rigid inner and outer layers can be constructed of any type of plastic, carbon fiber or other composite material. The layers can further include any complementing forward viewing contours, see at 130 for outer layer 124 and at 132 for inner layer 122 so as to provide an adequate field of vision for the wearer. A faceguard of non-limiting design is depicted by width extending portions 134 and 136 and crosswise extending reinforcing portions 138 and 140. Support pads 140 and 142 are also shown located between the wearer's head and inner mounting surfaces of the inner rigid helmet layer 122 (these being representative of any arrangement of interior supporting pads or cushions for supporting the inner helmet or shell upon the wearer's head).

[0065] The construction of the dual layer helmet is further such that headset components including a receiver and/or microphone can be mounted within the space between the inner and outer rigid layers, this being a desirous feature in sporting events such as football or auto racing. The support tendons 126 and 128 (also again termed as support columns as also depicted in related FIGS. 21 and 23) are constructed of any resilient and deformable material, typically a plastic composite, exhibiting the necessary properties of stretch-ability and which enable the outer rigid layer or shell 124 to stretch in energy absorptive fashion relative to the inner layer by virtue of the plurality of perimeter located tendons.

[0066] As further shown, the tendons 126 and 128 are each constructed of a semi-rigid deformable and resilient material, such as including but not limited to any type of plastic selected from a polypropylene material with fiber or other reinforcement, as well as potentially including any of a thermoplastic elastomer (TPE), thermoplastic vulcanizate (TPV) or other construction which provides a desirable degree of flex and/or bend in response to impact events to the outer helmet 124 and to minimize transference to the inner helmet 122 and the wearer's skull and spine. Each of the tendons/columns 126 and 128 further includes a generally polygonal cross sectional, shown as a modified tubular or cylindrical shaped intermediate stem, and which terminates in flattened engaging portions which can be mechanically or chemically secured to opposing surface locations of the outer and inner rigid layers (see inner surface locations of outer rigid layer

124 with inner spaced and outer facing locations of inner layer **122**). Without limitation, the elastic tendons can exhibit any other shape or profile which facilitates the resilient and spatially arrayed mounting structure between the inner and outer helmet layers.

[0067] FIG. 13 is a side line art view of the dual layer helmet of FIG. 12 and illustrating an arrangement of the inner bridging support tendons, see at **144**, **146**, **148** and **150**, arranged between the inner **122** and outer **124** rigid layers. An additional side located support tendon **152** is shown, with an opposite side located tendon being hidden from view, with the understanding that any number of tendons can be arranged in three dimensional spaced fashion across the separation zone between the inner and outer rigid helmets according to the dynamic environment in which the helmet is utilized. As further defined herein, the term “column” or “support tendon” is intended to include (but not be limited to) any linking component or structure which serves to spatially support the outer helmet or shell **124** around the inner helmet or shell **122**, but to do so in such a manner that the tends/columns provide multi-dimensional flex, bend or deformation in response to externally applied impact forces, preventing these impact forces from being directly transferred to the inner helmet **122** and, by extension, the wearers skull, neck and cervical spinal connections, and further doing so in a fashion which provides snap-back or return to the original configuration (i.e. resiliency) upon the force being dissipated or absorbed by the tendon structure.

[0068] Also depicted are impact support portions, at **154**, **156**, **158** and **160**, incorporated into the inner rigid layer **122** (i.e. supporting the exterior locations of the wearers head and skull), these being located proximate the mounting locations of the indicated flexible tendons **144**, **146**, **148** and **150** upon the exterior locations of the inner helmet or shell **122**. The impact support portions **154-160** can be constructed of any composite or other force absorbing material, such also potentially including a control collapsible structural foam.

[0069] FIG. 14 is a side cutaway of the helmet of FIG. 12 in a pre-impact condition and which again illustrates the engagement structure of the elastic tendons (see in particular the flattened mounting profiles **162** and **164** of selected tendon **144**. Also depicted at **166** is a minimal separation distance established between the lower rear edge of the outer shell **124** and the back 6 (see also FIG. 10) of the wearer, for which the helmet construction provides support in response to a rear rotating of the helmet towards an impact condition with the back).

[0070] FIG. 15 is a succeeding view to FIG. 14 and illustrating the dynamic deflecting characteristics of the elastic tendon supported outer helmet in response to a forward impact event, see arrow **168**. In this depiction, the forward most located support tendon **150** compresses in a fashion which permits the outer rigid helmet layer **124** to collapse in a force absorptive and attenuating fashion in a direction towards the inner helmet layer **122**. The rearward spaced tendons **148**, **146** and **144** are further shown stretching to varying degrees with the lower/rearward most tendon **144** stretching a maximum distance in which the cross sectional dimensions of the tendon are reduced. The elastic nature of the tendons is further such that the deflection forces exerted upon the outer shell **124** are countered by opposite and attenuating tension forces exerted by the tendons.

[0071] FIG. 16 is an alternate view to FIG. 15 illustrating the dynamic deflecting characteristics of the elastic tendon

supported outer helmet in response to a rear impact event, see arrow **170**. In this illustration, the elastic tendons/columns **144**, **146**, **148** and **150** displace in an opposite (forward) direction, with the forward most tendon **150** stretching forwardly and downwardly in the manner shown. As with the forward impact event of FIG. 15, the rear impact generated event of FIG. 16 is countered by reverse forces exerted by the elastic tendons (e.g. the resilient properties of the tendons absorbing and countering the initial force in a dampening fashion to protect the wearer).

[0072] FIG. 17 is an alternate view to FIGS. 15 and 16 and illustrating a side impact event (see arrow **172**) in which the outer shell **124** is depicted in a (side) lateral displacing and force attenuating condition. The ability to absorb a lateral directed force in the manner shown in FIG. 17 (see compressed side tendon **126** and elongated opposite side tendon **128**) enables the wearer's head to avoid absorbing a significant degree of the forces associated with the impact, and such as which can otherwise be transferred to the wearer's neck and spinal column.

[0073] Proceeding to FIG. 18, an illustration is shown at of a dual layer helmet construction according to a third embodiment and illustrating a foam insert **176** positioned between the inner **122** and outer **124** rigid layers, similar to as previously described however alternative to the support tendons shown in FIG. 12. The foam insert **176** provides impact protection between the inner and outer rigid helmet layers and, without limitation, can include any type of soft, rigid or structural/collapsible composition. The construction of the inner **122** and outer **124** helmet layers can also include any of those previously described (e.g. including an impact resistant plastic such as a heavy duty polypropylene or like material which can include a talc or fiber combination to enhance strength) and can further include any other shape or size.

[0074] FIG. 19 is a cutaway view of the helmet shown in FIG. 18 and better illustrating the inner **122** and outer **124** rigid helmet layers and intermediate foam support with interior air circulation and venting characteristics, and the inner cushioning pad support **176**, this further being configured between the inner rigid helmet layer and the surface of the wearers head so as to include an air circulation network (see selected perimeter extending main channel **178** in two dimensional cutaway with outer **180** and inner **182** spaced cross channels for providing ventilation to the user's head). Also again shown are inner structural pads associated with the inner helmet layer **122** and such as shown at **158** which are arranged in such a way that they do not impede the ventilation aspects of the helmet assembly. Also depicted at **177** and **179** are earholes defined by inner perimeter surfaces configured within the foam insert or pad support **176**, and which communicate with one or more of the main ventilation channels **178** as well as aligning side holes **181** and **183** in the outer helmet which communicate through additional aligning holes (see inner perimeter walls **181'** and **183'**) in the inner helmet.

[0075] FIG. 20 is a succeeding illustration to FIG. 19 and illustrating the dynamic characteristics of the helmet in response to a side-impact event (see directional arrow **184**), in which the outer rigid layer **124** is shifted laterally in the direction shown and so that the foam construction **176** absorbs the impact forces in an attenuating and counter exerting fashion (see compression of foam on left side of helmet) to prevent unnecessary forces being exerted against the user's head and neck (see contact location **185** between the helmet side edge and shoulder which minimizes the degree of bend-

ing motion absorbed by the user's head). Also again depicted are ear hole locations again established by inner perimeter walls in the foam **186** and **188**.

[0076] Proceeding now to FIG. **21**, an illustration **190** is generally referenced of a partial illustration of a dual layer helmet (including outer helmet **192** and inner helmet **194**) according to a yet further variant and further showing an energy absorbing column support (tendon) **196** of similar construction to that previously described and extending between the layers or shells **192/194** such that, and upon the outer helmet experiencing an impact event, the assembly provides for multi-directional energy absorbing properties. As previously described, the tendons or supports can exhibit any desired force dampening or attenuation structure which facilitates multi-dimensional displacement of the outer helmet **192**, in response to an impact event, while minimizing the force transferred to the inner helmet (layer or shell) **194** and the wearer's head via the inner supporting cushioning locations, see further at **195**.

[0077] FIG. **22** is a further rotated partial perspective in cutaway of the helmet of FIG. **21** and illustrating a dual compression (coil) spring arrangement, see springs **198** and **200** associated with a given face mask mounting location with the outer helmet, such providing for bi-directional force absorbing displacement. A selected face mask portion, depicted by extending curved member **202** includes, at selected cutaway end mounting location, an annular protuberance **204** which separates the springs **198** and **200**.

[0078] As further shown, a seating profile is defined in the outer shell **192** within which the end portion of the mask member **202** is displaceably supported. The three dimensional profile exhibits annular ends or abutment ledges, at **202** and **204**, which (upon seating the end mounting portion of the mask member **202**) compress opposite ends of the springs **198** and **200**, depending upon the direction of displacement of the mask (see bidirectional arrow **206** representing either of a pushing or pulling force exerted upon the mask member **202**). Without limitation, a similar arrangement is configured at the opposite mounting end of mask member **202**, as well as first and second corresponding mounting ends of a lower extending mask member **208**.

[0079] Proceeding to FIG. **23**, a front view is shown of a related helmet construction, generally at **210**, which is similar to that depicted in FIG. **21** (as well as the related variant of FIGS. **12-20**). FIG. **23** illustrates a modified construction of a force absorbing component arranged in combination with the energy absorbing column support or tendon previously identified at **196** for supporting inner **214** and outer **212** helmet layers in spatial fashion. An additional component **216** is illustrated on an opposite side of the helmet construction and exhibits an outer or circular shaped disk with first/outer **218** and second/inner **220** flattened mounting locations securing to the opposing locations of the helmets/shells **212** and **214**, again for providing optimal force deflection/absorption of impact forces exerted against the outer helmet **212**.

[0080] FIG. **24** is partial frontal side illustration of a modification of the force absorbing component in the form of an outer or circular disk portion **222** in combination with an inner integrally configured cross configuration **224** for providing optimal force deflection/absorption of impact forces exerted against the outer helmet, again at **212**, relative to the spatially and inner supported helmet **214**. FIG. **25** is a similar view to FIG. **24** and depicting a selected force absorbing component in the configuration of an internally hollow sphere

226. FIG. **26** presents a yet further variant of force absorbing component in the form of first **228** and second **230** disks arranged in rotatably offset and overlapping/intersecting fashion.

[0081] The examples of FIGS. **24-26** are intended to be representative of alternative constructions to that depicted in FIGS. **23**, with particular reference to the ring or disk shaped deflecting or force absorbing elements. As with the tendon/column **196**, the other shapes also include a resilient plasticized construction and can be configured to provide any desired force absorbing properties consistent with that described above.

[0082] Having described my invention, other and additional preferred embodiments will become apparent to those skilled in the art to which it pertains, and without deviating from the scope of the appended claims:

I claim:

1. A force attenuating helmet construction, comprising:
 - a rigid wearable shell generally conforming to a wearer's head;
 - a plurality of force absorbing and reacting portions extending from locations of said rigid layer;
 - said force absorbing and reacting portions including at least one inner perimeter extending cushion ring supported upon an inside of said rigid layer; and
 - said force absorbing and reacting portions further including at least one exterior mounted cushioning member supported along a lower rim edge of said rigid layer via a plurality of dynamic force absorbing and counter exerting springs such that, in response to an impact event experienced by said helmet, said absorptive and reactive forces minimizing impact forces transferred to the user's head and spine.
2. The helmet construction as described in claim 1, said exterior mounted cushioning member further comprising a plurality of three cushioning portions, each exhibiting an inner contoured surface from which extends said springs in spaced apart fashion, said cushioning members collectively projecting in at least a partially exterior direction from the lower rim of said rigid shell and which are adapted to contact at least one of shoulder, back and neck locations of the wearer in order to attenuate the bending motions of the user's head.
3. The helmet construction as described in claim 1, said force absorbing and reacting portions further comprising a combination of internal supported cushioning components associated with said rigid layer and including at least one of a top inner located compressible bladder.
4. The helmet construction as described in claim 1, said at least one inner perimeter extending cushion ring further comprising an intermediate extending cushioning ring constructed of a plurality of interconnected and individually ballasted members.
5. The helmet construction as described in claim 4, further comprising a perimeter extending inner support structure for said cushion ring.
6. The helmet construction as described in claim 5, said inner support structure further comprising spaced apart and circular extending cables, between which are configured crosswise extending and spaced apart interconnecting cables.
7. The helmet construction as described in claim 1, said force absorbing and reacting portions further comprising a pair of cheek bone located cushioning support members.
8. The helmet construction as described in claim 7, said cheek bone cushioning support members each further com-

prising an inner surface projecting array of stem supported compressible portions, upon which are mounted upper extending end and increased diameter annular portions which, upon contacting the wearer, deform in a collective combined bending and compressing/widening fashion.

9. The helmet construction as described in claim 3, said top inner bladder further comprising a pseudo pancake configuration with upper and lower flattened portions which are interconnected by an intermediate bridging stem portion, said top inner bladder providing controlled collapse and reformable valving structure such that a hollow interior associated with said bladder deforms in a force attenuating fashion, following which it self-refills and resets with a ballasting fluid.

10. The helmet construction as described in claim 4, said inner and intermediate extending cushioning ring further comprising a plurality of individual collapsible portions provided in the circular ring array, each of said collapsible portions exhibiting a soft plastic and which includes a bi-directional valve for providing controlled collapse in response to a force application.

11. The helmet construction as described in claim 1, said force absorbing and reacting portions further comprising a lower and rear perimeter extending ring supported upon an inside extending location of said rigid shell and adapted to supporting the rear base of the skull and the upper connecting location of the spinal column.

12. An impact attenuation helmet construction, comprising:

- a rigid outer shell;
- a rigid inner shell adapted to being worn upon a wearer's head and arranged a spatially separated distance from said outer shell; and
- a plurality of resilient plasticized members extending between said inner and outer shells in a three dimensional array in order to spatially support said outer shell a distance from an outer surface of said inner shell.

13. The helmet construction of claim 12, said resilient plasticized members further comprising at least one support tendons constructed of any resilient and elastic material including any of a thermoplastic elastomer (TPE), thermo-

plastic vulcanizate (TPV) or other construction which provides a desirable degree of flex and/or bend in response to impact events to said outer shell.

14. The helmet construction as described in claim 13, said support tendons each further comprising a generally polygonal cross sectional shaped intermediate stem terminating in flattened engaging portions which can be mechanically or chemically secured to opposing surface locations of said outer and inner rigid layers.

15. The helmet construction as described in claim 12, further comprising at least one cushioning support applied to an inner surface of said inner shell.

16. The helmet construction as described in claim 12, further comprising dual compression coil associated with a mounting location of an extending end of a face mask portion with said outer shell for providing for bi-directional force absorbing displacement of said mask portion, a seating profile being defined in said outer shell, within which an end portion of said mask portion is displaceably supported.

17. The helmet construction as described in claim 12, said support tendons each further comprising a circular shaped disk with outer and inner flattened mounting locations securing to opposing locations of said inner and outer shells.

18. The helmet construction as described in claim 12, said support tendons each further comprising an outer or circular disk portion in combination with an inner integrally configured cross configuration with outer and inner flattened mounting locations securing to opposing locations of said inner and outer shells.

19. The helmet construction as described in claim 12, said support tendons each further comprising an internally hollow sphere with outer and inner flattened mounting locations securing to opposing locations of said inner and outer shells.

20. The helmet construction as described in claim 12, said support tendons each further comprising first and second circular shaped disks arranged in rotatably offset and overlapping/intersecting fashion and with outer and inner flattened mounting locations securing to opposing locations of said inner and outer shells.

* * * * *